

**DESCRIPTION**

General use acrylic paint, high quality, and durability.

**PROPERTIES**

- Viscosity: 18-25sec (Flow Cup DIN4, 20°C)
- Density: 0.6-0.8 g/L (Density Cup 100cm<sup>3</sup>/20°C, ASTM D – 1475)
- VOC content : 650 g/L
- Flash Point: -104°C
- Drying time  
(1 Layer, Temperature 20°C, Humidity <65%):
  - Touch: 5-10min
  - Through dry: 1h
  - Maximum hardness: 24h
- Coverage: 3m<sup>2</sup>/0.4L, 7.5m<sup>2</sup>/L
- GLOSS (GLOSS METER 60°ASTM D – 1471):
  - 60-95 GLOSS UNITS/GLOSS
  - 10-60 GLOSS UNITS/SEMI GLOSS - SATIN
  - 0-10 GLOSS UNITS/MATT
- Film thickness: 100µm (wet), 25-30µm (dry)
- Can Pressure: 4bar (20°C), 8 bar (50°C)
- Contents: 400ml & 500ml  
(500ml-for certain shades)

**INSTRUCTIONS FOR USE****APPLICATION**

Remove all dust, rust, and oil from the surface. Protect the area which you don't want to be painted. Shake the can thoroughly and spray at a distance of 25-30cm from the surface. Try the spray on testing surface. For better results apply 2-3 thin coats, 3-5 min apart.

**Best application temperature: 10°C - 25°C.**

**AFTER USE**

Spray holding the can inverted for 3". Clean the caps with solvent

**STORAGE**

5-35°C. Do not put in vehicles.

**CAP SYSTEM****SMART CAP**

- Less overspray
- Extreme Coverage
- Fast drying
- Hard chisel lines
- Even coating
- Suitably for effects
- Dual way spraying

**SAFETY**



Request SDS

\*Cap indicates the color of the can.







## COLOR RANGE

|                                                                                                                              |                                                                                                                                |                                                                                                                                 |
|------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| RAL 1007   DAFFODIL YELLOW<br>CL 321<br>—   | RAL 5002   ULTRAMARINE BLUE<br>CL 417<br>—   | RAL 7042   TRAFFIC GREY A<br>CL 306<br>—     |
| RAL 1013   OYSTER WHITE<br>CL 415<br>—      | RAL 5010   GENTIAN BLUE<br>CL 316<br>—       | RAL 8000   GREEN BROWN<br>CL 466<br>—        |
| RAL 1014   IVORY<br>CL 302<br>—             | RAL 5012   LIGHT BLUE<br>CL 317<br>—         | RAL 8003   CLAY BROWN<br>CL 324<br>—         |
| RAL 1015   LIGHT IVORY<br>CL 347<br>—       | RAL 5013   COBALT BLUE<br>CL 413<br>—        | RAL 8004   COPPER BROWN<br>CL 414<br>—       |
| RAL 1018   ZINC YELLOW<br>CL 313<br>—       | RAL 5017   TRAFFIC BLUE<br>CL 341<br>—       | RAL 8011   NUT BROWN<br>CL 315<br>—          |
| RAL 1023   TRAFFIC YELLOW<br>CL 453<br>—    | RAL 5018   TURQUOISE BLUE<br>CL 418<br>—     | RAL 8016   MAHOGANY BROWN<br>CL 416<br>—     |
| RAL 1028   MELON YELLOW<br>CL 320<br>—      | RAL 6001   EMERALD GREEN<br>CL 462<br>—      | RAL 8017   CHOCOLATE BROWN<br>CL 318<br>—    |
| RAL 2003   PASTEL ORANGE<br>CL 329<br>—     | RAL 6002   LEAF GREEN<br>CL 460<br>—         | RAL 8019   GREY BROWN<br>CL 419<br>—         |
| RAL 2010   SIGNAL ORANGE<br>CL 331<br>—    | RAL 6005   MOSS GREEN<br>CL 314<br>—        | RAL 9001   CREAM<br>CL 425<br>—             |
| RAL 3000   FLAME RED<br>CL 330<br>—       | RAL 6009   FIR GREEN<br>CL 455<br>—        | RAL 9002   GREY WHITE<br>CL 412<br>—       |
| RAL 3003   RUBY RED<br>CL 311<br>—        | RAL 6018   YELLOW GREEN<br>CL 463<br>—     | RAL 9003   SIGNAL WHITE<br>CL 426<br>—     |
| RAL 3004   PURPLE RED<br>CL 464<br>—      | RAL 6028   PINE GREEN<br>CL 428<br>—       | RAL 9005   GLOSS BLACK<br>CL 303<br>—      |
| RAL 3009   OXIDE RED<br>CL 325<br>—       | RAL 7001   SILVER GREY<br>CL 411<br>—      | RAL 9005   SEMIGLOSS BLACK<br>CL 323<br>—  |
| RAL 3015   LIGHT PINK<br>CL 465<br>—      | RAL 7011   IRON GREY<br>CL 305<br>—        | RAL 9005   MATT BLACK<br>CL 304<br>—       |
| RAL 3020   TRAFFIC RED<br>CL 312<br>—     | RAL 7016   ANTHRACITE GREY<br>CL 322<br>—  | RAL 9007   GREY ALUMINIUM<br>CL 427<br>—   |
| RAL 4003   HEATHER VIOLET<br>CL 468<br>—  | RAL 7021   BLACK GREY<br>CL 420<br>—       | RAL 9010   GLOSS WHITE<br>CL 300<br>—      |
| RAL 4005   BLUE LILAC<br>CL 469<br>—      | RAL 7035   LIGHT GREY<br>CL 319<br>—       | RAL 9010   MATT WHITE<br>CL 301<br>—       |

## CONTAINER 500ml

|                                                                                                                         |                                                                                                                          |                                                                                                                           |
|-------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| RAL 9010   GLOSS WHITE<br>N300<br>—  | RAL 9010   MATT WHITE<br>N301<br>—   | RAL 9005   GLOSS BLACK<br>N303<br>—  |
| RAL 9005   MATT BLACK<br>N304<br>—   | RAL 3020   TRAFFIC RED<br>N312<br>—  |                                                                                                                           |

There are likely to be declinations in digital performance of shades.

ISSUED DATE: 20/9/2024

VERSION: 02