

**DESCRIPTION**

Semi-transparent colored varnishes in aerosol form. Ideal for painting and protection of wooden surfaces. It can be used on painted or non-painted wooden furniture and any wooden objects.

**PROPERTIES**

- Viscosity: 18-25sec (Flow Cup DIN4, 20°C)
- Density: 0.8-1.1 g/L (Density Cup 100cm<sup>3</sup>/20°C, ASTM D – 1475)
- VOC content: 779 g/L
- Flash Point: -104°C (based on propellant)
- Drying time
  - Touch (20°C, Humidity<65%): 5-10min
  - Through dry (20°C, Humidity <65%): 1h
  - Maximum hardness: 24h
- Coverage: 5m<sup>2</sup>/L
- Gloss: 80-90 GLOSS UNIT (GLOSS METER 60°ASTM D – 1471)
- Can Pressure: 4bar (20°C), 8 bar (50°C)
- Contents: 400ml

**INSTRUCTIONS FOR USE****APPLICATION**

Remove all dust and oil from the surface. Protect the area which you don't want to be painted. Shake the can thoroughly and spray at a distance of 25-30cm from the surface. Try the spray on testing surface. For better results apply 2-3 thin coats, 3-5 min apart.

**Best application temperature: 10-25°C.**

High moisture levels affect drying time and the final gloss.

**AFTER USE**

Spray holding the can inverted for 3". Clean the caps with solvent.

**STORAGE**

Store between 5-35°C. Do not store in vehicles.

**CAP SYSTEM****SMART CAP**

- Less overspray
- Extreme Coverage
- Fast drying
- Hard chisel lines
- Even coating
- Suitably for effects
- Dual way spraying

**SAFETY**

Request SDS

**COLOR RANGE**

601 MAHOGANY



603 WALNUT



604 OAK



607 TEAK

